

## **Digital Mini Incubator 10L**

## **COMPACT SPACE-SAVING DESIGN**

The digital incubator offers an economical and space saving solution for microbiology or hematology applications.

Exterior Dimensions:  $11.2 \times 11 \times 13.2$ "

Interior Dimensions:  $9 \times 7.9 \times 7.9$ "

Temperature Uniformity:  $\pm 0.5$  at 37°C

Temperature Accuracy:  $\pm 0.5$  at 37°C

**Temperature Range:** Ambient +5°C to +70°C

Voltage: 115V or 230V

Certifications: 230V model is CE marked



**Digital Controls:** The temperature can be freely adjusted in increments of 0.1°C up to a maximum of 70°C. Heating elements are incorporated into the housing base and walls to ensure temperature stability and uniformity.

**Personal-Sized:** The door of the incubator has a transparent Plexiglas® window to provide full visibility to samples. The housing and door frame are constructed entirely of epoxy coated mild steel for strength and durability.

## **Axelerist Financial**

80 Business Park Dr., Ste. 209 Armonk, NY 10504 United States (914) 253-8840 info@axelerist.com

## Axelerist B.V.

Westplein 12 12-14 3016BM Rotterdam The Netherlands 0031 (0)10 30 70 217 info@axelerist.com



Equipping You for Success.

www.axelerist.com